

AGRIMAX RT 955

| | |
|---------------------|-------------------------------------------------------|
| TIRE SIZE | 340/85 R 48 |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 152 A8/B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 353 | RIM REC | W 12 |
| OD (MM) | 1797 | RIM ALT | W 11 |
| SLR (MM) | 855 | ECE | E4-106R-000800 |
| RC (MM) | 5572 | SRI | 875 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1385 | 1815 | 2205 | 2415 | 2560 | 2805 | 3055 | 3305 | 3550 | - |
| 40 | 1385 | 1815 | 2205 | 2415 | 2560 | 2805 | 3055 | 3305 | 3550 | - |
| 30 | 1485 | 1940 | 2360 | 2585 | 2740 | 3005 | 3270 | 3535 | 3800 | - |
| 10 | 1655 | 2080 | 2560 | 3040 | 3515 | 3625 | 4050 | 4475 | 4900 | 5325 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.