

FLOTATION 648

| | |
|---------------------------|---|
| TIRE SIZE | 500/50 - 17 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 139 A8/135 B |
| LI/SS FREE ROLLING | 152 A8/148 B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94040353 | RC (IN) | 108.3 |
| SW (IN) | 20.1 | RIM REC | 16.00 |
| OD (IN) | 37.2 | ECE | E4-106R-001886 |
| SLR (IN) | 16.4 | PR | 16 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 44 | 45 | 46 |
|-----------|-------|-------|-------|
| 5 FR | 10560 | 10760 | 10960 |
| 10 FR | 9500 | 9680 | 9870 |
| 20 FR | 8440 | 8610 | 8760 |
| 25 FR | 7540 | 7680 | 7830 |
| 30 FR | 6790 | 6910 | 6940 |
| 5 DW | 7220 | 7360 | 7500 |
| 10 DW | 6500 | 6620 | 6750 |
| 20 DW | 5780 | 5890 | 6000 |
| 25 DW | 5160 | 5260 | 5360 |
| 30 DW | 4640 | 4730 | 4810 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.