

# FLOTATION 648

<b>TIRE SIZE</b>	500/50 - 17
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	145 A8/141 B
<b>LI/SS FREE ROLLING</b>	157 A8/154 B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94040346	<b>RC (IN)</b>	108.3
<b>SW (IN)</b>	20.1	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	37.2	<b>ECE</b>	E4-106R-002305
<b>SLR (IN)</b>	16.4	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	55	57	58
5 FR	12360	12540	12730
10 FR	11120	11290	11460
20 FR	9890	10040	10180
25 FR	8830	8960	9090
30 FR	7950	8070	8270
5 DW	8690	8810	8950
10 DW	7810	7930	8060
20 DW	6960	7050	7160
25 DW	6210	6290	6390
30 DW	5590	5670	5680

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.