

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>260/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	113 A8/B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	258	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	872	<b>RIM ALT</b>	9 ; W 9
<b>SLR (MM)</b>	402	<b>ECE</b>	E4-106R-000640
<b>RC (MM)</b>	2639	<b>SRI</b>	425

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	545	625	715	805	900	990	1070	1150
40	545	625	715	805	900	990	1070	1150
30	585	670	770	865	965	1065	1150	1235
10 LT	730	835	960	1085	1210	1330	1440	1545
10 HT	585	670	770	865	965	1065	1150	1235

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.