

FLOTATION 648

TIRE SIZE	850/50 - 30.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	174 A8/170 B
LI/SS FREE ROLLING	186 A8/182 B



ABMESSUNGEN US STANDARD

USA-CODE	94006588	RC (IN)	194.3
SW (IN)	33.5	RIM REC	AG 28.00
OD (IN)	65.0	ECE	E4-106R-002284
SLR (IN)	28.0	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
5 FR	26080	27730	29320
10 FR	23470	24950	26390
20 FR	20870	22190	23460
25 FR	18630	19810	20940
30 FR	16770	17820	18740
5 DW	18400	19550	20680
10 DW	16560	17590	18610
20 DW	14720	15640	16540
25 DW	13140	13970	14770
30 DW	11830	12570	13230

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.