


# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>750/70 R 26</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MIETITREBBIA / SPARGITORE / TRATTORE / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	172 A8/B



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	780	<b>RIM REC</b>	DW 25 B
<b>OD (MM)</b>	1750	<b>RIM ALT</b>	DW 24 B
<b>SLR (MM)</b>	785	<b>ECE</b>	E11-106R-007934
<b>RC (MM)</b>	5269	<b>SRI</b>	825

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
50	2710	3150	3595	4035	4475	4915	5420	5735	6300	-	-
40	2710	3150	3595	4035	4475	4915	5420	5735	6300	-	-
30	2905	3375	3850	4320	4795	5265	5805	6145	6750	-	-
10 LT	3635	4225	4820	5410	6000	6595	7270	7690	8450	-	-
10 HT	2905	3375	3850	4320	4795	5265	5805	6145	6750	-	-
10 CYC	-	5065	5775	6480	7190	7900	8710	9215	10125	10285	10710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.