


# AGRIMAX FORCE



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>IF 710/75 R 42</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | HARVESTER / HIGH-POWER TRACTOR<br>/ TRACTOR  |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 181 D  |

## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94060085 | <b>RC (IN)</b> | 252.1           |
| <b>SW (IN)</b>  | 28.2     | <b>RIM REC</b> | DW 25 B         |
| <b>OD (IN)</b>  | 84.0     | <b>RIM ALT</b> | DW 23 B         |
| <b>SLR (IN)</b> | 38.1     | <b>ECE</b>     | E11-106R-006490 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI            | 9     | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|----------------------|-------|-------|-------|-------|-------|-------|-------|-------|
| 45                   | 7790  | 8930  | 10250 | 11580 | 12910 | 14230 | 15550 | 16540 |
| <b>FROM 40 TO 25</b> | 8540  | 9820  | 11280 | 12730 | 14190 | 15640 | 17100 | 18200 |
| 20                   | 8880  | 10210 | 11720 | 13240 | 14750 | 16260 | 17780 | 18910 |
| 12                   | 9230  | 10600 | 12170 | 13750 | 15310 | 16890 | 18460 | 19640 |
| 5                    | 10850 | 12470 | 14320 | 16160 | 18010 | 19860 | 21700 | 23090 |
| <b>UPTO 20 CYC</b>   | 11100 | 12760 | 14650 | 16540 | 18440 | 20330 | 22220 | 23640 |
| <b>UPTO 10 CYC</b>   | 13240 | 15220 | 17470 | 19730 | 21980 | 24240 | 26500 | 28180 |
| <b>UPTO 5 CYC</b>    | 14520 | 16690 | 19170 | 21640 | 24110 | 26590 | 29060 | 30920 |
| 5 HT                 | 8880  | 10210 | 11720 | 13240 | 14750 | 16260 | 17780 | 18910 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.