


AGRIMAX SPARGO SB

TIRE SIZE	VF 320/105 R 54 CFO
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATTORE
VERSIONE	STEEL BELTED
TIRE TYPE	TL
LI/SS	172 D



DIMENSIONI IS STANDARD

SW (MM)	335	RIM REC	DW11
OD (MM)	2045	RIM ALT	DW10; W11
SLR (MM)	941	ECE	E11-106R-0011738
RC (MM)	6268	SRI	975

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
70	2470	2755	3100	3385	3530	3730	3815	3960	4160	4360	4535	4705	4850	4990	5135	5280	5510	5735
FROM 65 TO 40	2710	3025	3405	3720	3875	4095	4190	4350	4570	4790	4980	5170	5325	5485	5640	5800	6050	6300
30	2765	3090	3475	3795	3955	4180	4280	4440	4665	4890	5080	5275	5435	5595	5755	5920	6175	6430
20	2820	3150	3540	3870	4035	4265	4360	4525	4755	4985	5180	5380	5540	5705	5870	6035	6295	6555
10	2980	3330	3745	4090	4265	4505	4610	4785	5025	5270	5475	5685	5860	6030	6205	6380	6655	6930
UPTO 30 CYC	3080	3435	3865	4225	4405	4655	4760	4940	5190	5440	5655	5870	6050	6225	6405	6585	6870	7155
UPTO 15 CYC	3675	4100	4615	5040	5255	5555	5680	5895	6195	6495	6750	7005	7220	7430	7645	7860	8200	8540
UPTO 10 CYC	4025	4495	5055	5525	5760	6085	6225	6460	6790	7115	7395	7680	7910	8145	8380	8615	8990	9360
10 HT	2765	3090	3475	3795	3955	4180	4280	4440	4665	4890	5080	5275	5435	5595	5755	5920	6175	6430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.