


# AGRIMAX V- FLECTO

|              |  |
|--------------|--|
| TIRE SIZE    | VF 480/60 R 28   |
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | MOTORSTARK TRAKTOR / TRAKTOR   |
| VERSION      | STANDARD   |
| TIRE TYPE    | TL   |
| LI/SS        | 145 D  |



## DIMENSIONER US STANDARD

|          |          |         |                 |
|----------|----------|---------|-----------------|
| USA CODE | 94060740 | RC (IN) | 149.9           |
| SW (IN)  | 18.5     | RIM REC | DW 16 L         |
| OD (IN)  | 50.8     | RIM ALT | W 16 L          |
| SLR (IN) | 22.5     | ECE     | E11-106R-005496 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI                     | 9    | 12   | 15   | 17   | 20   | 23   |
|-------------------------------|------|------|------|------|------|------|
| 45                            | 3200 | 3710 | 4230 | 4760 | 5280 | 5810 |
| FROM 40 TO 25                 | 3520 | 4090 | 4660 | 5240 | 5810 | 6395 |
| 20                            | 3580 | 4170 | 4750 | 5330 | 5920 | 6510 |
| 12                            | 3650 | 4240 | 4840 | 5450 | 6040 | 6650 |
| 5                             | 3860 | 4500 | 5130 | 5750 | 6380 | 7030 |
| *UPTO 5 CYC WITH FRONT LOADER | 4920 | 5720 | 6530 | 7330 | 8120 | 8950 |
| 5 HT                          | 3580 | 4170 | 4750 | 5330 | 5920 | 6510 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.