


AGRIMAX RT 855

TIRE SIZE	420/80 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	151 D ; 162 A2



DIMENSIUNI IS STANDARD

SW (MM)	418	RIM REC	W 13
OD (MM)	1840	RIM ALT	W 12
SLR (MM)	863	ECE	E4-106R-001730
RC (MM)	5641	SRI	900

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1625	1865	2140	2415	2695	2970	3210	3450
50	1705	1960	2250	2540	2830	3120	3375	3625
40	1780	2045	2345	2650	2950	3255	3520	3780
30	1870	2145	2465	2780	3100	3415	3695	3970
10	2235	2565	2945	3325	3705	4085	4420	4750
10 LT	2175	2500	2870	3240	3610	3980	4305	4625
10 HT	1870	2145	2465	2780	3100	3415	3695	3970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.