

AGRIMAX V- FLECTO

TYRE SIZE	VF 710/65 R 46 NRO
UM	US STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	188 D



DIMENSIONS US STANDARD

USA CODE	94522330	RC (IN)	248.42
SW (IN)	29.05	RIM REC	DW 25 B
OD (IN)	82.48	RIM ALT	DW 23 B ; MW 25 B
SLR (IN)	37.14	ECE	E11-106R-0011961

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
45	8820	10140	11680	13230	14330	15650	17420	18740	20500	22050
FROM 40 TO 25	8820	10140	11680	13230	14330	15650	17420	18740	20500	22050
20	8990	10350	11930	13490	14620	15970	17770	19110	20920	22490
12	9170	10550	12160	13760	14900	16280	18120	19490	21330	22930
5	9700	11150	12850	14550	15760	17220	19160	20610	22550	24250
UPTO 20 CYC&NBSP;	10010	11520	13270	15010	16270	17770	19770	21270	23280	25020
UPTO 10 CYC&NBSP;	11950	13750	15840	17920	19420	21220	23600	25400	27790	29870
UPTO 5 CYC&NBSP;	13090	15070	17360	19640	21280	23250	25870	27830	30460	32740
5 HT	8990	10350	11930	13490	14620	15970	17770	19110	20920	22490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.