


# EARTHMAX SR 35

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>875/65 R 29</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | ARTICULATED DUMP TRUCK / LOADER<br>/ DOZER   |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 214 A2   |



## DIMENSIONS IS STANDARD

|                 |            |                    |                      |
|-----------------|------------|--------------------|----------------------|
| <b>OD (MM)</b>  | 1860       | <b>RIM ALT</b>     | 27.00/3.0; 28.00/3.5 |
| <b>SLR (MM)</b> | 816        | <b>TRA CODE</b>    | L3                   |
| <b>RC (MM)</b>  | 5559       | <b>STAR RATING</b> | ★                    |
| <b>RIM REC</b>  | 27.00/3.50 |                    |                      |

## LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 4.00  | 4.25  | 4.50  | 4.75  |
|------------|-------|-------|-------|-------|
| 10         | 18500 | 19500 | 20600 | 21200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.