DATA SHEET

PRINTED ON
21-04-2026

AS 504

TYRE SIZE	**6.00 - 16**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	IMPLEMENTS
VERSION	STANDARD
TYRE TYPE	TT
LI/SS DRIVE WHEEL	83 A8
LI/SS FREE ROLLING	95 A8

DIMENSIONS IS STANDARD

SW (MM)	164	**RIM REC**	4.00 E
OD (MM)	735	**RIM ALT**	4.50 E; 4½ K
SLR (MM)	343	**ECE**	E4-106R-002836
RC (MM)	2190	**PR**	6

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	2.80
10 FR	965
25 FR	820
30 FR	775
40 FR	690
10 DW	680
25 DW	575
30 DW	545
40 DW	485

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..