


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>650/65 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINEYARD HARVESTER / TRACTOR / HARVESTER
<b>VERSION</b>	SPECIAL
<b>TL/TT</b>	TL
<b>LI/SS</b>	163 D ; 166 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	645	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1811	<b>RIM ALT</b>	DW 21 B ; DW 23 B
<b>SLR (MM)</b>	830	<b>ECE</b>	E4-106R-000624
<b>RC (MM)</b>	5483	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	2340	2730	3075	3415	3755	4050	4485	4875
<b>50</b>	2460	2870	3230	3585	3945	4250	4715	5120
<b>40</b>	2545	2970	3340	3710	4085	4400	4880	5300
<b>30</b>	2695	3145	3535	3930	4320	4660	5165	5610
<b>10 LT</b>	3140	3660	4120	4575	5035	5425	6015	6535
<b>10 HT</b>	2695	3145	3535	3930	4320	4660	5165	5610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.