

FL 630 SUPER

TIRE SIZE	650/65 R 30.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	РАЗБРАСЫВАТЕЛЬ / АВТОЦИСТЕРНА / ПРИЦЕП / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	176 D



РАЗМЕРЫ US STANDARD

USA CODE	94045594	RC (IN)	195.9
SW (IN)	25.4	RIM REC	AG 20.00
OD (IN)	63.8	ECE	E4-106R-001653
SLR (IN)	28.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	4560	5280	6000	7270	8410	9700	10980	11840	13120	14250
40	5020	5800	6580	7990	9240	10650	12060	13000	14410	15650
30	6070	7020	7960	9670	11190	12890	14590	15730	17440	18950
25	6820	7890	8950	10870	12570	14480	16400	17680	19600	21300
15	7930	9160	10390	12620	14590	16820	19050	20530	22760	24730
5	9020	10430	11840	14370	16630	19170	21700	23390	25920	28170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.