


# EARTHMAX SR 53

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 29.5 R 29  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | PLANIERER / RADLADER / FLACHE<br>DUMPER  |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND (UMS)   |
| <b>TIRE TYPE</b>    | TL   |



## ABMESSUNGEN IS STANDARD

|                 |           |                    |           |
|-----------------|-----------|--------------------|-----------|
| <b>OD (MM)</b>  | 2015      | <b>RIM ALT</b>     | 24.00/3.5 |
| <b>SLR (MM)</b> | 905       | <b>TRA CODE</b>    | L5        |
| <b>RC (MM)</b>  | 6059      | <b>STAR RATING</b> | ★★        |
| <b>RIM REC</b>  | 25.00/3.5 |                    |           |

## LOAD CAPACITY (KG/TIRE)

|                   |   |
|-------------------|---|
| <b>KM/H / BAR</b> | - |
| -                 | - |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.