

# RIB 774 (A)

<b>TIRE SIZE</b>	<b>200/60 - 14.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	PRESĂ DE BALOTAT / MAȘINĂ DE RECOLTARE / REMORCĂ / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	113 A8



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94010981	<b>RC (IN)</b>	74.3
<b>SW (IN)</b>	8.3	<b>RIM REC</b>	AG 6.75
<b>OD (IN)</b>	24.0	<b>ECE</b>	E11-106R-003608
<b>SLR (IN)</b>	11.3	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>102</b>
5 FR	3350
15 FR	3020
20 FR	2840
25 FR	2540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.