

AGRIMAX SIRIO

TIRE SIZE	IF 600/70 R 30
UM	IS STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	HIGH SPEED
TL/TT	TL
LI/SS	165 D ; 162 E



DIMENSIONS IS STANDARD

SW (MM)	603	ECE	E4-106R-000817
OD (MM)	1602	SRI	750
SLR (MM)	713	TRA CODE	R1W
RC (MM)	4759	TREAD DEPTH (MM)	57,5
RIM REC	DW 21 B	TKPH (US) (TM/H)	0
RIM ALT	DW 20 B		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2200	2525	2900	3280	3650	4025	4350	4685
FROM 65 TO 40	2420	2780	3190	3605	4015	4425	4785	5150
30	2515	2890	3315	3745	4175	4600	4975	5355
25	2565	2945	3380	3820	4255	4690	5165	5560
20	2610	3000	3445	3890	4355	4775	5165	5560
10	3070	3530	4050	4575	5095	5615	6075	6540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.