

# AGRIMAX RT 855

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>420/80 R 46</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |   |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>      | SPECIAL   |
| <b>TL/TT</b>        | TL  |
| <b>LI/SS</b>        | 159 D ; 170 A2  |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 418  | <b>RIM REC</b> | W 13           |
| <b>OD (MM)</b>  | 1840 | <b>RIM ALT</b> | W 12           |
| <b>SLR (MM)</b> | 863  | <b>ECE</b>     | E4-106R-001489 |
| <b>RC (MM)</b>  | 5641 | <b>SRI</b>     | 900            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 65         | 1625 | 1865 | 2140 | 2415 | 2695 | 2970 | 3210 | 3450 | 4070 | 4375 |
| 50         | 1705 | 1960 | 2250 | 2540 | 2830 | 3120 | 3375 | 3625 | 4275 | 4595 |
| 40         | 1780 | 2045 | 2345 | 2650 | 2950 | 3255 | 3520 | 3780 | 4460 | 4795 |
| 30         | 1870 | 2145 | 2465 | 2780 | 3100 | 3415 | 3695 | 3970 | 4685 | 5035 |
| 10         | 2235 | 2565 | 2945 | 3325 | 3705 | 4085 | 4420 | 4750 | 5580 | 6000 |
| 10 LT      | 2175 | 2500 | 2870 | 3240 | 3610 | 3980 | 4305 | 4625 | 5455 | 5865 |
| 10 HT      | 1870 | 2145 | 2465 | 2780 | 3100 | 3415 | 3695 | 3970 | 4685 | 5035 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.