


AGRIMAX FORCE



TIRE SIZE	IF 750/75 R 46
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MIETITREBBIA / TRATTORE A ELEVATA POTENZA / TRATTORE
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	186 D

DIMENSIONI IS STANDARD

SW (MM)	742	RIM REC	DW 25 B
OD (MM)	2294	ECE	E11-106R-006491
SLR (MM)	1032	SRI	1075
RC (MM)	6802	TRA CODE	R1W

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	4060	4665	5355	6050	6740	7430	8125	8645
FROM 65 TO 40	4465	5130	5890	6650	7410	8170	8930	9500
30	4640	5335	6125	6915	7705	8495	9285	9880
20	4820	5540	6360	7180	8000	8820	9640	10260
10	5670	6515	7480	8445	9410	10370	11340	12065
UPTO 30 CYC	5800	6665	7655	8645	9630	10620	11605	12350
UPTO 15 CYC	6920	7950	9125	10305	11485	12660	13840	14725
UPTO 10 CYC	7590	8720	10010	11305	12595	13885	15180	16150
10HT	4640	5335	6125	6915	7705	8495	9285	9880

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.