

# FLOTATION 648

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>850/50 - 30.5</b>   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | PRESSA PER BALLE DI FIENO /<br>MIETITREBBIA / SPARGITORE /<br>MIETITREBBIA / ATTREZZI AGRICOLI |
| <b>VERSIONE</b>           | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 168 A8/164 B   |
| <b>LI/SS FREE ROLLING</b> | 180 A8/176 B   |



## DIMENSIONI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 850  | <b>RIM REC</b> | AG 28.00        |
| <b>OD (MM)</b>  | 1650 | <b>ECE</b>     | E11-106R-004564 |
| <b>SLR (MM)</b> | 710  | <b>PR</b>      | 12              |
| <b>RC (MM)</b>  | 4935 |                |                 |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.10 | 1.30  | 1.50  |
|------------|------|-------|-------|
| 10 FR      | 9345 | 10305 | 11200 |
| 20 FR      | 8410 | 9275  | 10080 |
| 30 FR      | 7475 | 8245  | 8960  |
| 40 FR      | 6675 | 7360  | 8000  |
| 50 FR      | 6010 | 6625  | 7100  |
| 10 DW      | 6540 | 7210  | 7840  |
| 20 DW      | 5885 | 6490  | 7055  |
| 30 DW      | 5230 | 5770  | 6270  |
| 40 DW      | 4670 | 5150  | 5600  |
| 50 DW      | 4205 | 4635  | 5000  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.