


# AGRIMAX V-FLECTO



TIRE SIZE	VF 620/70 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	175 D

## РАЗМЕРЫ US STANDARD

USA CODE	94514229	RC (IN)	228.1
SW (IN)	24.4	RIM REC	DW 21 B
OD (IN)	76.2	RIM ALT	DW 20 B; DW 23 B
SLR (IN)	33.4	ECE	E11-106R-0010829

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6920	8020	9140	10380	11490	12600	13830
FROM 40 TO 25	7610	8830	10040	11410	12630	13840	15210
20	7760	9010	10240	11640	12870	14120	15510
12	7910	9180	10450	11870	13140	14400	15820
5	8370	9710	11040	12550	13890	15230	16730
UPTO 20 CYC	8630	10020	11400	12950	14330	15720	17260
UPTO 10 CYC	10310	11960	13600	15450	17110	18750	20600
UPTO 5 CYC	11300	13110	14910	16940	18750	20560	22590
5 HT	7760	9010	10240	11640	12870	14120	15510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.