


FL 695

MEDIDA DEL NEUMÁTICO	710/50 R 30.5
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	REMOLQUE / MAQUINARIA AGRÍCOLA / REMOLQUE
VERSIÓN	STEEL BELTED
TIRE TYPE	TL
LI/SS	177 D



DIMENSIONES IS STANDARD

SW (MM)	700	RIM REC	AG24.00
OD (MM)	1490	RIM ALT	AG20.00
SLR (MM)	691	ECE	E11-106R-008661
RC (MM)	4553	SRI	700

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
65	--	--	--	3725	4310	4895	5405	5915	6500	6935	7300
50	--	--	--	4510	5215	5920	6540	7160	7865	8395	8835
40	--	3675	4470	5065	5860	6655	7350	8045	8840	9435	9930
30	3200	4080	4965	5625	6505	7390	8160	8935	9815	10475	11025
25	3350	4270	5195	5885	6810	7730	8640	9345	10270	10960	11535
20	3495	4460	5425	6145	7110	8075	8915	9760	10725	11445	12045
10	3815	4865	5915	6705	7755	8805	9725	10645	11695	12485	13140

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.