



Latest update  
2-06-2026

DATA SHEET

# BK-LOADER 53

|                     |                    |
|---------------------|--------------------|
| <b>TIRE SIZE</b>    | <b>365/70 R 18</b> |
| <b>UM</b>           | US STANDARD        |
| <b>CONSTRUCTION</b> |                    |
| <b>MACHINERY</b>    | LOADER             |
| <b>VERSION</b>      | ARAMID BELTED      |
| <b>TL/TT</b>        | TL                 |
| <b>LI/SS</b>        | 146A2/142A4        |



## DIMENSIONS US STANDARD

|                 |          |                |       |
|-----------------|----------|----------------|-------|
| <b>USA CODE</b> | 94074143 | <b>RC (IN)</b> | 118.8 |
| <b>SW (IN)</b>  | 14.2     | <b>RIM REC</b> | 11    |
| <b>OD (IN)</b>  | 39.0     |                |       |
| <b>SLR (IN)</b> | 18.0     |                |       |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 22   | 29   | 36   | 44   | 51   | 58   | 65   | 73   | 80    |
|-----------|------|------|------|------|------|------|------|------|-------|
| 12        | 2060 | 2640 | 3100 | 3580 | 4090 | 4510 | 4980 | 5380 | 5850  |
| 5         | 2320 | 2980 | 3510 | 4040 | 4630 | 5100 | 5630 | 6090 | 6620  |
| STATIC    | 3690 | 4740 | 5580 | 6420 | 7370 | 8110 | 8940 | 9680 | 10520 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.