

# FLOTATION 647

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>260/75 - 15.3</b>                                       |
| <b>UM</b>                 | US STANDARD  |
| <b>CONSTRUCTION</b>       | ⊠ BIAS   |
| <b>MACHINERY</b>          | LANDWIRTSCHAFTLICHE GERÄTE /<br>LANDWIRTSCHAFTLICHE GERÄTE |
| <b>VERSION</b>            | STANDARD   |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 119 A8   |
| <b>LI/SS FREE ROLLING</b> | 131 A8   |



## ABMESSUNGEN US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA-CODE</b> | 94062768 | <b>RC (IN)</b> | 93.7            |
| <b>SW (IN)</b>  | 10.8     | <b>RIM REC</b> | 9.00            |
| <b>OD (IN)</b>  | 30.9     | <b>ECE</b>     | E11-106R-005838 |
| <b>SLR (IN)</b> | 14.3     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>80</b> |
|------------------|-----------|
| 25 FR            | 4300      |
| 25 DW            | 3000      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.