DATA SHEET

PRINTED ON
23-04-2026

FLOTATION 648

TIRE SIZE	**600/55 - 26.5**
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / РАЗБРАСЫВАТЕЛЬ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	160 A8/157 B
LI/SS FREE ROLLING	172 A6/169 B

РАЗМЕРЫ US STANDARD

USA CODE	94030972	**RC (IN)**	158.1
SW (IN)	24.1	**RIM REC**	AG 20.00
OD (IN)	53.3	**ECE**	E11-106R-004556
SLR (IN)	22.9	**PR**	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	39	41	42
5 FR	18640	19050	19440
10 FR	16780	17140	17500
20 FR	14910	15230	15550
25 FR	13320	13600	13890
30 FR	11980	12250	12790
5 DW	13320	13610	13890
10 DW	11980	12250	12500
20 DW	10660	10890	11110
25 DW	9510	9720	9920
30 DW	8560	8750	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..