

## RT 857

|                  |                    |
|------------------|--------------------|
| <b>TIRE SIZE</b> | <b>420/85 R 30</b> |
| <b>UM</b>        | IS STANDARD        |
| <b>MACHINERY</b> | TRACTOR            |
| <b>VERSION</b>   | STANDARD           |
| <b>TIRE TYPE</b> | TL                 |
| <b>LI/SS</b>     | 140 A8/B           |

### ABMESSUNGEN IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 450  | <b>RIM REC</b> | W 15 L         |
| <b>OD (MM)</b>  | 1476 | <b>RIM ALT</b> | W 14 L ; W 13  |
| <b>SLR (MM)</b> | 656  | <b>ECE</b>     | E4-106R-001394 |
| <b>RC (MM)</b>  | 4398 | <b>SRI</b>     | 700            |

### LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 1375 | 1600 | 1825 | 2050 | 2275 | 2500 |
| 40         | 1375 | 1600 | 1825 | 2050 | 2275 | 2500 |
| 30         | 1475 | 1715 | 1955 | 2195 | 2435 | 2675 |
| 10LT       | 1845 | 2145 | 2450 | 2750 | 3050 | 3350 |
| 10HT       | 1475 | 1715 | 1955 | 2195 | 2435 | 2675 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

