


AW 711

| | |
|---------------------|---|
| TIRE SIZE | 440/55 R 18 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| VERSION | STUBBLE RESISTANT |
| TIRE TYPE | TL |
| LI/SS | 159 A8/B |



DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 410 | RIM REC | 14 |
| OD (MM) | 945 | RIM ALT | 13 |
| SLR (MM) | 432 | ECE | E4-106R-001398 |
| RC (MM) | 2893 | SRI | 450 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 1315 | 1710 | 2100 | 2410 | 2800 | 3195 | 3415 | 3765 | 4115 | 4375 |
| 40 | 1315 | 1710 | 2100 | 2410 | 2800 | 3195 | 3415 | 3765 | 4115 | 4375 |
| 30 | 1470 | 1915 | 2355 | 2695 | 3140 | 3580 | 3825 | 4215 | 4610 | 4900 |
| 25 | 1565 | 2035 | 2505 | 2870 | 3335 | 3805 | 4065 | 4485 | 4900 | 5210 |
| 20 | 1655 | 2155 | 2650 | 3035 | 3530 | 4030 | 4305 | 4745 | 5185 | 5515 |
| 10 | 1840 | 2390 | 2940 | 3370 | 3920 | 4475 | 4780 | 5270 | 5760 | 6125 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.