

# FS 216

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>30.5L - 32</b>                             |
| <b>UM</b>           | IS STANDARD                                   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | TRATOR FLORESTAL SKIDDER /<br>AUTOCARREGADORA |
| <b>VERSÃO</b>       | STEEL BELTED                                  |
| <b>TIRE TYPE</b>    | TL  |



## DIMENSÕES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 775  | <b>RIM REC</b> | DH 27           |
| <b>OD (MM)</b>  | 1847 | <b>RIM ALT</b> | DH 27 B         |
| <b>SLR (MM)</b> | 833  | <b>ECE</b>     | E11-106R-003426 |
| <b>RC (MM)</b>  | 5466 | <b>PR</b>      | 16              |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>2.10</b> | <b>1.70</b> |
|-------------------|-------------|-------------|
| <b>10</b>         | 7450        | -           |
| <b>30</b>         | -           | 5300        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.