

AGRIMAX V-FLECTO

TYRE SIZE	VF 900/65 R 46 CFO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	SPECIAL
TL/TT	TL
LI/SS	193 D



DIMENSIONS US STANDARD

USA CODE	94513734	RC (IN)	271.1
SW (IN)	36.2	RIM REC	DW 30B
OD (IN)	91.1	ECE	E11-106R-0011166
SLR (IN)	39.5		

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29
45	11760	13600	15450	17530	19150	20760	23070
FROM 40 TO 25	12930	14960	16990	19270	21040	22820	25350
20	13180	15260	17320	19640	21460	23270	25860
12	13440	15550	17660	20030	21880	23720	26370
5	14220	16450	18680	21190	23140	25100	27890
UPTO 20 CYC	14670	16960	19270	21860	23870	25890	28770
UPTO 10 CYC	17510	20260	23000	26100	28500	30910	34350
UPTO 5CYC	19190	22200	25220	28600	31240	33870	37640
5 HT	13180	15260	17320	19640	21460	23270	25860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.