

# XL GRIP IND3 (RTG)

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 21.00 - 35  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | КОНТЕЙНЕРНЫЙ<br>ПЕРЕГРУЖАТЕЛЬ НА<br>ПНЕВМОКОЛЕСНОМ ХОДУ |
| <b>VERSION</b>      | INDUSTRIAL  |
| <b>TIRE TYPE</b>    | TL  |



## РАЗМЕРЫ IS STANDARD

|                 |           |                 |      |
|-----------------|-----------|-----------------|------|
| <b>OD (MM)</b>  | 2020      | <b>PR</b>       | 40   |
| <b>SLR (MM)</b> | 928       | <b>TRA CODE</b> | IND3 |
| <b>RC (MM)</b>  | 5980      |                 |      |
| <b>RIM REC</b>  | 15.00/3.0 |                 |      |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>9.90</b> |
| 10                | 32800       |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.