


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>340/65 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR / VINDIMADORA / CEIFEIRA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	124 D ; 127 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	343	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	950	<b>RIM ALT</b>	W 10 ; W 12
<b>SLR (MM)</b>	430	<b>ECE</b>	E4-106R-001413
<b>RC (MM)</b>	2892	<b>SRI</b>	450

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	755	880	1010	1120	1235	1330	1475	1600
50	790	925	1060	1180	1295	1395	1550	1680
40	825	965	1105	1225	1350	1455	1610	1750
30	865	1015	1160	1290	1420	1530	1695	1840
10 LT	1010	1180	1355	1505	1655	1785	1975	2145
10 HT	865	1015	1160	1290	1420	1530	1695	1840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.