


EARTHMAX SR 22 AS

TIRE SIZE	23.5 R 25
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HJULLASTARE / VÄGHYVLARE
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	185 B ; 170 A8 ; 201 A2



DIMENSIONER IS STANDARD

OD (MM)	1614	TRA CODE	E2/G2/L2
SLR (MM)	709	STAR RATING	★★/★/★★
RC (MM)	4863		
RIM REC	19.50/2.5		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	4.00	4.25	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25
50	-	-	-	-	-	-	-	-	7500	7750	8250	8500	9000	9250	-	-	-	-
40	3150	3550	4000	4500	4875	5300	5600	6000	-	-	-	-	-	-	-	-	-	-
10	-	-	-	-	-	-	-	-	-	-	-	-	-	12500	12850	13200	13600	14000
KM/H / BAR	6.50																	
50	-																	
40	-																	
10	14500																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.