


FL 630 ULTRA

| | |
|---------------------|--|
| TIRE SIZE | 710/40 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ÉPANDEUR / VÉHICULE CITERNE / REMORQUE / OUTILLAGE AGRICOLE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 161 D ; 172 A8 |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| CODE USA | 94052905 | RC (IN) | 137.4 |
| SW (IN) | 28.6 | RIM REC | AG 24.00 |
| OD (IN) | 44.9 | ECE | E11-106R-003016 |
| SLR (IN) | 20.2 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|
| 45 | 2980 | 3390 | 3810 | 4740 | 5390 | 6230 | 7050 | 7700 | 8450 | 9280 |
| 40 | 3260 | 3730 | 4190 | 5200 | 5920 | 6830 | 7750 | 8470 | 9280 | 10200 |
| 30 | 3960 | 4520 | 5070 | 6300 | 7160 | 8280 | 9390 | 10250 | 11240 | 12350 |
| 25 | 4450 | 5080 | 5700 | 7090 | 8060 | 9310 | 10560 | 11530 | 12640 | 13890 |
| 20 | 4940 | 5630 | 6320 | 7860 | 8940 | 10320 | 11710 | 12790 | 14020 | 15400 |
| 15 | 5160 | 5890 | 6610 | 8220 | 9350 | 10800 | 12260 | 13380 | 14670 | 16110 |
| 5 | 5870 | 6700 | 7530 | 9370 | 10650 | 12300 | 13950 | 15230 | 16710 | 18350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.