


RIDEMAX IT 696

| | |
|---------------------|--|
| TYRE SIZE | 440/80 R 30 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRACTOR |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 157 A8 ; 153 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 441 | RIM REC | W 14 L |
| OD (MM) | 1466 | RIM ALT | W 15 L |
| SLR (MM) | 668 | ECE | E4-106R-002297 |
| RC (MM) | 4456 | SRI | 700 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 1715 | 2115 | 2480 | 2885 | 3250 | 3650 |
| 50 | 1825 | 2250 | 2640 | 3065 | 3455 | 3880 |
| 40 | 1940 | 2395 | 2805 | 3260 | 3670 | 4125 |
| 30 | 2020 | 2495 | 2925 | 3395 | 3825 | 4300 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.