


AGRIMAX V- FLECTO

TIRE SIZE	VF 650/70 R 34 NRO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HOCHLEISTUNGSTRAKTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	170 D



ABMESSUNGEN US STANDARD

USA-CODE	94074785	RC (IN)	197.8
SW (IN)	23.7	RIM REC	DW 21 B
OD (IN)	67.1	RIM ALT	DW 20 B
SLR (IN)	29.1	ECE	E11-106R-008813

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6020	6980	7940	9030	9990	10950	12040
FROM 40 TO 25	6610	7670	8730	9920	10980	12040	13230
20	6750	7810	8900	10120	11190	12270	13490
12	6880	7970	9070	10320	11410	12510	13760
5	7270	8430	9600	10910	12070	13240	14550
*UPTO 5 CYC WITH FRONT LOADER	9260	10740	12210	13890	15370	16840	18520
5 HT	6750	7810	8900	10120	11190	12270	13490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.