

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>420/85 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	142 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94021741	<b>RC (IN)</b>	185.1
<b>SW (IN)</b>	17.2	<b>RIM REC</b>	W 15 L
<b>OD (IN)</b>	62.1	<b>RIM ALT</b>	W 13; W 14 L
<b>SLR (IN)</b>	27.9	<b>ECE</b>	E4-106R-000656

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
<b>30</b>	3220	3750	4270	4790	5320	5840
<b>25</b>	3220	3750	4270	4790	5320	5840
<b>20</b>	3450	4010	4570	5140	5700	6260
<b>5 LT</b>	4320	5030	5730	6440	7140	7840
<b>5 HT</b>	3450	4010	4570	5140	5700	6260

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.