

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/55 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	151 A8/ 148 B
<b>LI/SS FREE ROLLING</b>	164 A8/160 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94006410	<b>RC (IN)</b>	146.3
<b>SW (IN)</b>	23.6	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	48.4	<b>ECE</b>	E11-106R-004553
<b>SLR (IN)</b>	21.3	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	25	29
5 FR	13040	14030	15430
10 FR	11740	12620	13890
20 FR	10430	11220	12350
25 FR	9310	10020	11020
30 FR	8390	9020	9920
5 DW	8990	9680	10650
10 DW	8100	8710	9580
20 DW	7200	7740	8520
25 DW	6430	6910	7610
30 DW	5790	6220	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.