


AGRIMAX RT 657

TIRE SIZE	540/65 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	150 D ; 153 A8



DIMENSIONS IS STANDARD

SW (MM)	530	RIM REC	W 16 L
OD (MM)	1464	RIM ALT	W 18 L
SLR (MM)	670	ECE	E4-106R-000651
RC (MM)	4403	SRI	700

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1610	1880	2115	2345	2580	2785	3085	3350
50	1690	1975	2220	2465	2715	2925	3240	3520
40	1755	2045	2300	2555	2815	3030	3360	3650
30	1855	2160	2430	2700	2970	3200	3550	3855
10 LT	2160	2515	2830	3145	3460	3730	4135	4490
10 HT	1855	2160	2430	2700	2970	3200	3550	3855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.