DATA SHEET

PRINTED ON
23-04-2026

AGRIMAX RT 765

TYRE SIZE	**300/70 R 20**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	120 A8/B

DIMENSIONS IS STANDARD

SW (MM)	295	**RIM REC**	W 9
OD (MM)	952	**RIM ALT**	W 10
SLR (MM)	428	**ECE**	E4-106R-000643
RC (MM)	2854	**SRI**	450

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	660	760	870	980	1095	1205	1305	1400
40	660	760	870	980	1095	1205	1305	1400
30	705	810	930	1050	1170	1290	1395	1500
10 LT	885	1020	1170	1320	1470	1620	1750	1880
10 HT	705	810	930	1050	1170	1290	1395	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..