

# MP 590

<b>TIRE SIZE</b>	<b>18 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ВИЛОЧНЫЙ ПОГРУЗЧИК / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ / АГРОПРОМЫШЛЕННЫЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	480	<b>RIM REC</b>	14.0
<b>OD (MM)</b>	1190	<b>ECE</b>	E11-106R-004408
<b>SLR (MM)</b>	530	<b>PR</b>	20
<b>RC (MM)</b>	3534		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>7.50</b>
<b>40 DW</b>	5800
<b>30 DW</b>	6500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.