


# AGRIMAX RT 765

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>260/70 R 20</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> |  RADIAL            |
| <b>MACHINERY</b>    | PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| <b>VERSION</b>      | SPECIAL   |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 113 A8/B  |



## DIMENSIUNI US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94044221 | <b>RC (IN)</b> | 103.9          |
| <b>SW (IN)</b>  | 10.2     | <b>RIM REC</b> | W 8            |
| <b>OD (IN)</b>  | 34.3     | <b>RIM ALT</b> | 9; W 9         |
| <b>SLR (IN)</b> | 15.8     | <b>ECE</b>     | E4-106R-000640 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI   | 9    | 12   | 15   | 17   | 20   | 23   | 29   | 35   |
|-------------|------|------|------|------|------|------|------|------|
| <b>30</b>   | 1200 | 1380 | 1580 | 1770 | 1980 | 2180 | 2360 | 2540 |
| <b>25</b>   | 1200 | 1380 | 1580 | 1770 | 1980 | 2180 | 2360 | 2540 |
| <b>20</b>   | 1290 | 1480 | 1700 | 1910 | 2130 | 2350 | 2540 | 2720 |
| <b>5 LT</b> | 1610 | 1840 | 2120 | 2390 | 2670 | 2930 | 3170 | 3410 |
| <b>5 HT</b> | 1290 | 1480 | 1700 | 1910 | 2130 | 2350 | 2540 | 2720 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.