

# AGRIMAX RT 855

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>420/85 R 38</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | BESPRUTNINGSBIL / SKÖRDEMASKIN<br>FÖR VINGÅRD / TRAKTOR /<br>SKÖRDEMASKIN / ARBETSFORDON |
| <b>VERSION</b>      | SPECIAL  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 144 A8/B   |



## DIMENSIONER IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 438  | <b>RIM REC</b> | W 15 L         |
| <b>OD (MM)</b>  | 1679 | <b>RIM ALT</b> | W 13 ; W 14 L  |
| <b>SLR (MM)</b> | 763  | <b>ECE</b>     | E4-106R-000661 |
| <b>RC (MM)</b>  | 5014 | <b>SRI</b>     | 800            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 1540 | 1795 | 2045 | 2300 | 2550 | 2800 |
| 40         | 1540 | 1795 | 2045 | 2300 | 2550 | 2800 |
| 30         | 1650 | 1920 | 2190 | 2460 | 2730 | 3000 |
| 10 LT      | 2070 | 2405 | 2745 | 3080 | 3420 | 3755 |
| 10 HT      | 1650 | 1920 | 2190 | 2460 | 2730 | 3000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.