


# AW 702

<b>TIRE SIZE</b>	<b>14.5/80 - 18</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	155 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94034666	<b>RC (IN)</b>	120.8
<b>SW (IN)</b>	14.7	<b>RIM REC</b>	11.0
<b>OD (IN)</b>	41.2	<b>RIM ALT</b>	12; 13
<b>SLR (IN)</b>	17.6	<b>ECE</b>	E11-106R-003601

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	49
5 FR	10030
15 FR	8530
20 FR	8020
25 FR	7160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.