

# AW 708

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | 500/50 - 17   |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | PRESSE À PAILLE / OUTILLAGE<br>AGRICOLE / REMORQUE /<br>MOISSONNEUSE / OUTILLAGE<br>AGRICOLE / REMORQUE |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS FREE ROLLING</b> | 140 A8  |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>CODE USA</b> | 94010363 | <b>RC (IN)</b> | 108.3          |
| <b>SW (IN)</b>  | 19.7     | <b>RIM REC</b> | 16.00          |
| <b>OD (IN)</b>  | 37.2     | <b>ECE</b>     | E4-106R-001884 |
| <b>SLR (IN)</b> | 16.4     | <b>PR</b>      | 10             |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>29</b> |
|------------------|-----------|
| 5 FR             | 7720      |
| 15 FR            | 6560      |
| 20 FR            | 6170      |
| 25 FR            | 5510      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.