

# FLOTATION 648

<b>TIRE SIZE</b>	<b>700/40 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALER / HAY HARVESTER / SPREADER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	148 A8/144 B
<b>LI/SS FREE ROLLING</b>	160 A8/ 157 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94006472	<b>RC (IN)</b>	139.3
<b>SW (IN)</b>	27.6	<b>RIM REC</b>	AG 24.00
<b>OD (IN)</b>	46.1	<b>ECE</b>	E11-106R-004554
<b>SLR (IN)</b>	20.1	<b>PR</b>	12

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	25
5 FR	12900	13410	13890
10 FR	11610	12070	12500
20 FR	10320	10720	11110
25 FR	9210	9580	9920
30 FR	8290	8620	9090
5 DW	9040	9380	9720
10 DW	8130	8440	8750
20 DW	7230	7510	7780
25 DW	6460	6700	6940
30 DW	5810	6030	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.