


RIB 713

| | |
|---------------------|--|
| TIRE SIZE | IF 240/80 R 15 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAQUINARIA AGRÍCOLA / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STUBBLE RESISTANT |
| TIRE TYPE | TL |
| LI/SS | 129 D |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|-----------------|-----------------|
| SW (MM) | 240 | RIM REC | W 8 |
| OD (MM) | 765 | ECE | E11-106R-002971 |
| SLR (MM) | 354 | SRI | 360 |
| RC (MM) | 2324 | TRA CODE | I1 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 5.0 |
|--------------------|-----|-----|-----|-----|------|------|------|------|------|------|
| FROM 10 TO 65 KM/H | 540 | 685 | 835 | 945 | 1095 | 1240 | 1370 | 1500 | 1650 | 1850 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.