


# AGRIMAX FORCE

<b>TIRE SIZE</b>	<b>IF 750/75 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН / ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	186 D



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94058082	<b>RC (IN)</b>	267.8
<b>SW (IN)</b>	29.2	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	90.3	<b>ECE</b>	E11-106R-006491
<b>SLR (IN)</b>	40.6	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8950	10280	11810	13340	14860	16380	17910	19060
<b>FROM 40 TO 25</b>	9840	11310	12980	14660	16340	18010	19690	20900
20	10230	11760	13500	15240	16990	18730	20470	21780
12	10630	12210	14020	15830	17640	19440	21250	22620
5	12500	14360	16490	18620	20740	22870	25000	26600
<b>UPTO 20 CYC</b>	12790	14690	16880	19060	21230	23410	25580	27230
<b>UPTO 10 CYC</b>	15260	17530	20120	22720	25320	27910	30510	32460
<b>UPTO 5 CYC</b>	16730	19220	22070	24920	27770	30610	33460	35600
5HT	10230	11760	13500	15240	16990	18730	20470	21780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.