


# AGRIMAX TERIS

**1050/50 R 32 CHO**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BIÇERDÖVER / PAMUK TOPLAMA MAKINESİ
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
	184 A8 ; 181 B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94076185	<b>RC (IN)</b>	223.8
<b>SW (IN)</b>	41.7	<b>RIM REC</b>	36.0 VA (multi-piece)
<b>OD (IN)</b>	74.5	<b>ECE</b>	E11-106R-0010258
<b>SLR (IN)</b>	33.1		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46
30	8190	9280	11640	12920	14370	15460	16920	18190
25	8930	10120	12700	14090	15670	16860	18450	19840
20	9560	10840	13590	15080	16780	18050	19750	21230
10 CYC	14740	16700	20950	23250	25870	27830	30460	32740
5 CYC	16070	18220	22860	25360	28220	30360	33220	35710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.