


AGRIMAX TERIS

TIRE SIZE	IF 580/80 R 34 CFO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ERNTMASCHINE / BAUMWOLLERNTEMASCHINE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	177 D



ABMESSUNGEN US STANDARD

USA-CODE	94044641	RC (IN)	213.5
SW (IN)	23.1	RIM REC	DW 20 B; DW 20 A
OD (IN)	70.6	RIM ALT	DW 21 A; DW 21 B
SLR (IN)	31.9	ECE	E4-106R-001833

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52
45	5430	6310	7190	8220	9090	9970	10990	11580	12760	14650	20040
FROM 40 TO 25	5970	6930	7900	9020	9990	10950	12070	12720	14010	16100	22030
20	6210	7210	8220	9390	10390	11390	12570	13240	14580	16750	22910
12	6440	7490	8530	9750	10790	11830	13040	13740	15130	17390	23790
5	7580	8800	10020	11460	12690	13920	15350	16160	17800	20450	27980
UPTO 20 CYC*	7750	9010	10270	11720	12980	14240	15700	16540	18210	20930	28620
UPTO 10 CYC*	9240	10740	12230	13980	15480	16970	18720	19710	21710	24950	34130
5 HT	6210	7210	8220	9390	10390	11390	12570	13240	14580	16750	22910

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.